

## mortising standards

### A Set Back

Standard	$\frac{5}{16}$ "
Option 1	$\frac{3}{4}$ "

### B Top Mortise Length

Standard	$\frac{5}{16}$ " x $3\frac{1}{4}$ "
Option 1	$\frac{5}{16}$ " x $4\frac{1}{4}$ "

### C Bottom Mortise Length

Standard	$\frac{5}{16}$ " x $1\frac{3}{4}$ "
Option 1	$\frac{5}{16}$ " x $3\frac{1}{4}$ "
Option 2	$\frac{5}{16}$ " x $4\frac{1}{4}$ "

### A Set Backs

All mortises are available with either the Standard or Option 1 Set Backs. For larger legs or when applying a bead moulding choose the Option 1 Set Back.

### B Top Mortise Length

Top blocks with a height equal to or greater than  $4\frac{1}{4}$ " choose Top Mortise in the Standard Length (for A400 aprons).

Top blocks with a height equal to or greater than 6" Top Mortise is available in either the Standard (for A400 aprons) or Option 1 Length (for A600 aprons).

### C Bottom Mortise Length

Stretcher and base blocks with a height less than  $4\frac{1}{4}$ " choose Bottom Mortise in the Standard Length (for stretcher stock).

For stretcher and base blocks with a height equal to or greater than 5" Bottom Mortise is available in either the Standard (for stretcher stock) or Option 1 Length (for A400 stock).

For stretcher and base blocks with a height equal to or greater than  $6\frac{1}{2}$ " Bottom Mortise is available in the Standard (for stretcher stock), Option 1 (for A400 stock) or Option 2 Length (for A600 stock).

